

6

Heavy Commercial Wood Effect Sheet Vinyl Flooring





The Forest fx collection of wood effect vinyl sheet floorcoverings is specifically designed for a wide range of commercial interiors. The contemporary and creative timber designs are ideal for education, healthcare, office, retail and leisure sectors, developed and presented in a practical, resilient and hygienic product construction.

The collections eclectic mix of traditional warm oak planks and cooler grey timbers creates an authentic wood palette that can be matched with a wide variety of interior design schemes, whilst the addition of two parquet effect designs adds to the collections versatility.

The durability of Forest fx lends itself perfectly to the demands of commercial interiors, leading with the key advantages of aesthetics and performance, with the added flexibility to meet corporate design schemes. Unique floor designs can easily be achieved by incorporating inlaid features and logos, managed by Polyflor's in house design team.





Heavy Commercial Wood Effect Sheet Vinyl Flooring

To further enhance the floorcovering, Forest fx features a high quality, cross-linked polyurethane reinforcement (PUR) providing a low cost, polish-free maintenance regime for the lifetime of the product.

Forest fx is 100% recyclable and achieves BRE A+ certification for major use areas based on a life cycle analysis approach over a building life of 60 years. All these qualities make the collection environmentally preferable whilst meeting decorative, practical, budgetary and maintenance objectives.











3106 Parish Oak Parquet

Plank size **76.2 x 288.6mm**







3104 Oslo Oak

Plank size 1**67 x 1500mm**

















2990 Oiled Oak

Plank size **167 x 1500mm**



Also availabl in acoustic





3109 Newport Oak

Plank size 167 x 1500mm

1





3102 Rural Deckwood

Plank size **180 x 1000mm**





3380 American Oak

Plank size **100 x 1000mm**



Also available in acoustic

2 Jan





3100 Classic Oak

Plank size 167 x 1500mm



0)) 19dB





3330 Rustic Oak

-

Plank size **84 x 332/664mm**



Also available in acoustic



W



3108 Eton Oak Parquet

Plank size **76.2 x 288.6mm**





3340 European Oak

Plank size 100 x 1000mm



Also available in acoustic





3120 French Walnut

Plank size **167 x 1000mm**





3150 Smoked Oak

Plank size **167 x 1500mm**



Also available in acoustic





3360 Mahogany

Plank size **84 x 332/664mm**









-











3990 Brazilian Walnut

Plank size **133 x 1000mm**



Forest *fx* COLLECTION

Forest fx represents the natural beauty and sophistication of wood in a practical and durable vinyl sheet format. This contemporary and wide-ranging palette is further enhanced by a variety of plank sizes, each carefully designed for natural authenticity.



3106 Parish Oak Parquet Plank size: 76.2 x 288.6mm



w/r 3103

LRV 37.0

w/r 2990

LRV 35.0



w/r 3113

LRV 41.7

w/r 3101

LRV 39.9

w/r 9838

LRV 29.9

3113 Blanched Oak Plank size: 200 x 1000mm



3104 Oslo Oak Plank size: 167 x 1500mm w/r 9829 LRV 31.9



3103 Rock Salt Oak Plank size: 220 x 1500mm



3101 Grey Sawmill Oak Plank size: 180 x 1000mm



3105 Alloyed Timber Plank size: 167 x 1500mm

w/r 9841 LRV 24.3



2990 Oiled Oak



3109 Newport Oak Plank size: 167 x 1500mm



3102 Rural Deckwood Plank size: 180 x 1000mm

w/r 3102 LRV 27.6

Plank size: 167 x 1500mm



w/r 3380

LRV 35.7

w/r 9822

LRV 23.6

LRV 14.0

3380 American Oak Plank size: 100 x 1000mm



LRV 28.6

w/r 3340

LRV 21.0

LRV 10.1

Plank size: 167 x 1500mm



3330 Rustic Oak Plank size: 84 x 332/664mm

w/r 3330 LRV 29.2



3108 Eton Oak Parquet Plank size: 76.2 x 288.6mm



3340 European Oak Plank size: 100 x 1000mm



3120 French Walnut Plank size: 167 x 1000mm

w/r 3120 LRV 17.0



3150 Smoked Oak Plank size: 167 x 1500mm



3360 Mahogany Plank size: 84 x 332/664mm



3990 Brazilian Walnut Plank size: 133 x 1000mm

w/r 3990 LRV 7.8





Polyflor have demonstrated a high level of commitment over the years to minimising our impact on the environment without compromising the performance benefits of our high quality floorcoverings.

There can be few materials better suited to recycling than vinyl flooring. Forest fx is 100% recyclable, and can be recycled many times over. Polyflor continually works on developing new products and technologies, and constantly evaluates production methods to further minimise our impact on the environment.



Maintenance & Hygiene

The incorporation of a polyurethane reinforcement into the Forest fx collection helps protect the floorcovering by resisting soiling and scuffing. Combined with the superior closed surface finish, this enhanced protection allows the use of a polish-free maintenance regime for the lifetime of the flooring.

This leads to an overall maintenance cost saving of 48% over a 20+ year life when compared to untreated heterogeneous flooring, and fewer cleaning chemicals and reduced power requirements mean reduced environmental impact.





Design Service

Polyflor has over 20 years experience in delivering floor design solutions. From simple tile patterns, borders and compass designs, to custom cut motifs.

We have helped architects and designers to realise stunning floors for hundreds of buildings, and our designers provide support throughout the project offering visuals, colour and product advice.

There is virtually no limit to the shapes, patterns or pictures you can create. We offer the precision and the flexibility of waterjet cutting to produce any design you require. School badges, information signs, corporate motifs; the possibilities are endless.

Fit for Purpose

In some large scale commercial interiors where the area is dualpurpose, the use of different types of floorcovering can help outline each zone to guide users.

For interiors where slip resistance is vital but only in certain zones, for example a school canteen, combining Polysafe slip resistant flooring in the food serving area with Forest fx wood effect in the dining area can help distinguish each of these zones, ensure Health & Safety is adhered to, and create a welcoming dining room for the children to relax in.





For detailed product and technical information on all commercial flooring collections within the Polyflor portfolio, visit polyflor.com where you can browse installation galleries, product specifications, brochures and all the latest news.



Free Sample Service

Polyflor provide a complementary product sample service, to ensure you find the exact floor you are looking for. To order your free samples of any of the Forest fx shades either visit the Polyflor website at polyflor.com, or call the dedicated Polyflor Samples Hotline on +44 (0)161 767 2551.

Contact Us

For general information on your specific project, speak with your local Polyflor provider. If you require detailed technical data, contact Polyflor Customer Technical Services on +44 (0)161 767 1912 or email tech@polyflor.com.

For details of international availability visit polyflor.com and follow the Contact Us link.

	Standards	Forest fx
Type of Floorcovering	EN 649/ISO 10582	Heterogeneous
Product Enhancement		PUR
Gauge	EN 428/ISO 24346	2.0mm
Wear Layer	EN 429/ISO 24340	0.70mm
Roll Size	EN 426/ISO 24341	2m x 20m = 40m ²
Total Weight	EN 430/ISO 23997	2700g/m²
General Performance	EN 649 ISO 10582	Conforms Conforms
Use Area	EN 685/ISO 10874	23, 34, 43
Resistance to Chemicals	EN 423	Excellent chemical resistance
Reaction to Fire	EN 13501-1	Class BfI-S1
Abrasion Resistance	EN 649 EN ISO 10582	Group T Type I
Slip Resistance*	EN 13893 AS/NZS 4586 DIN 51130	Class DS (dry condition) R10 R10
Residual Indentation	ISO 24343-1	<0.10mm
Castor Chair (continuous use)	EN 425/ISO 4918	Suitable
Dimensional Stability	EN 434/ISO 23999	<0.40%
Flexibility	EN 435/ISO 24344	(Method A) Pass 20mm Ø
Thermal Conductivity	_	Suitable for underfloor heating (max 27°C)
Electrical Behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
Light Fastness	ISO 105-B02	(Method 3) ≥6
VOC Emissions	Indoor Air Comfort GOLD AgBB VOC test Floorscore Swedish B.P.D. (FLEC test) GBCA/NZGBC Green Star IEQ-VOC	Eurofins certified product Very low emissions Certified Best Class Compliant
Responsible Sourcing	BES 6001	Very Good

Environmentally Preferable Flooring - Polyflor Forest fx PUR achieves a BRE Global A+ rating (ENP 415) in the Green Guide to Specification in use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Silver Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability.

Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

*For safety flooring with sustainable wet slip resistance, refer to Polysafe ranges.



Forest **f**x

POLYFLOR™ INTERNATIONAL

Australia

Polyflor Australia Tel: +613 9215 4400 Tel: 1800 777 425 E-mail: sales@polyflor.com.au

Canada

Polyflor Canada Inc. Tel: +1905 364 3000 E-mail: sales@polyflor.ca

China

Polyflor Hong Kong Tel: +(852) 2865 0101 E-mail: info@polyflor.com.hk

France

James Halstead France SAS Tel: +33 (0) 8 20 20 32 11 E-mail: info@jhfrance.fr

Germany

objectflor Art und Design Belags GmbH Tel: +49 (0) 2236 966 330 E-mail: info@objectflor.de India Polyflor India Pvt Ltd Tel: +91 22 4023 2485 E-mail: info@polyflor.co.in

Ireland Polyflor Ireland Tel: +353 (1) 864 9304 E-mail: salesireland@polyflor.com

New Zealand

Polyflor New Zealand Tel: +64 9 269 1111 Tel: 0800 765 935 E-mail: sales@polyflor.co.nz

Norway

Polyflor Nordic Tel: +47 23 00 84 00 E-mail: firmapost@polyflor.no

Poland Polflor Sp. Z o.o. Tel: +48 (0) 61 820 3155 E-mail: polyflor@polflor.com.pl

www.polyflor.com

Russia

Polyflor Contract Ltd Tel: +7 (812) 332 42 02 E-mail: info@polyflor.ru

South Africa

Poly Sales Africa (Pty.) Ltd Tel: +27 (0) 11609 3500 E-mail: info@polyflor.co.za

Sweden

FalckDesign AB Tel: +46 (0) 300 15820 E-mail: info@falckdesign.com

POLYFLOR[™] UK

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK

 UK SALES DIRECT:
 +44 (0)161 767 1122

 UK SAMPLE REQUESTS:
 +44 (0)161 767 2551

 EXPORT SALES DIRECT:
 +44 (0)161 767 1913

 UK FAX:
 +44 (0)161 767 1128

 EXPORT FAX:
 +44 (0)161 767 1166

 TECHNICAL SUPPORT:
 +44 (0)161 767 1912

 RECEPTION:
 +44 (0)161 767 1111

 E-MAIL:
 INF0@POLYFLOR.COM

 WEBSITE:
 WWW.POLYFLOR.COM



James Halitead FLOORING