## Polysafe Quattro PUR

Polysafe Quattro PUR is a heavy-duty, carborundum-free safety flooring with a flat emboss, designed to provide underfoot traction in continually wet areas. Available in either a solid colour or tonal chipped decoration, Quattro is ideally suited to both barefoot and shod traffic. Incorporating particles in the vinyl for sustainable wet slip resistance, Quattro offers enhanced protection in areas such as walk-in showers, wet rooms, disabled adaptations, hydrotherapy areas, spas, changing rooms and indoor swimming pool surrounds.



| Gauge  | EN 428/ISO 24346   | 2.0mm  |
|--|--|--|
| Roll Size  | EN 426/ISO 24341   | 2m x 20m = 40m <sup>2</sup>  |
| Total Weight   | EN 430/ISO 23997   | 2700g/m <sup>2</sup>   |
| General Performance  | EN 13845<br>ASTM F1303   | Conforms<br>Conforms   |
| Use Area   | EN 685/ISO 10874   |  |
| Resistance to Chemicals  | EN 423   | Good chemical resistance   |
| Water Tightness  | EN 13553   | Annex A  |
| Reaction to Fire   | EN 13501-1<br>ASTM E648<br>Australian BCA Spec C1.10-3   | Class BfI-S1<br>Class 1<br>Complies  |
| Abrasion Resistance  | EN 13845<br>EN 649   | 50,000 cycles<br>Group T   |
| Enhanced Slip Resistance   |  | ESb & ESf<br>P4<br>Class B<br>R1<br>Class B<br>R1<br>≥50 (wet test - 4S Rubber/Slider 96)<br>R2 ≥20µm<br>products is sustainable throughout the guaranteed<br>E Guidelines. For further clarification regarding slip |
| Electrical behaviour (body voltage)  | EN 1815  | ≤2kV Classified as 'antistatic'  |
| VOC Emissions  | AgBB VOC test<br>Floorscore<br>Finnish M1 Classification   | Pass<br>Certified<br>Certified   |
|  | with GreenRate level A - Gold Plus. Generic EN 15  | eneric A+ rating in major use areas such as educatior<br>5804 Environmental Product Declaration (EPD) availa<br>ne. Visit www.polyflor.com/sustainability.   |
| Polysafe PUR - Polysafe Quattro PUR features a hi cycle maintenance savings and optimum appearance |  | ent, UV cured to provide superior cleaning benefits, I<br>afe Quattro PUR should not have a polish applied.  |
|  |  | c flooring solution which can be confidently cleaned i<br>implementation of an effective cleaning regime is th   |
| and are suitable for steam cleaning on a periodic be   | asis. Chemical resistance charts available on requestance and product warranty, consult <b>Polyflor C</b><br>g. For latest information, please visit our website<br>various colours within the vinyl to impart the re- |  |
| 100% RECYCLABLE         CONTAINS RECYCLED MATERIAL         Image: Contains Recycled Material       |  | ofloor" floor<br>score<br>water  |
| BINT LEARNY NES SES SES  | UK manufactured  |  |
|  |  |  |

 Polyfor UK
 Sales Direct: +44 (0)161 767 1122 • Export Sales Direct: +44 (0)161 767 1913

 Sample Requests: +44 (0)161 767 2551 • email: info@polyflor.com • www.polyflor.com



 Polyflor Australia
 Tel: 1800 777 425 • email: sales@polyflor.com.au • www.polyflor.com.au

 Polyflor New Zealand
 Tel: 0800 765 935 • email: sales@polyflor.co.nz • www.polyflor.co.nz



EN 14041